



Retread Information

2/22/2008 #3 Technical Dept

Size	PR	Pattern	Buffing Radius (Inch)	Finished Tread Width (Inch)	Circumferential measure at 4/32nd undertread (Inch)	Brk Diameter + 8/32nd (mm)	Rim Width (Inch)
11.00R22	16	ST 508	24	9.1	135.8	1,098.6	8.00
11.00R24	16	ST 508	24	9.1	141.9	1,147.9	8.00
12.00R20	18	ST 508	24	9.3	134.1	1,084.8	8.50
10.00R20	16	ST 518	24	8.5	125.7	1,016.6	7.50
11.00R20	16	ST 518	26	9.0	129.3	1,045.8	8.00
11R22.5	16	ST 518	26	8.5	125.7	1,016.6	8.25
11R24.5	16	ST 518	26	8.5	132.1	1,068.4	8.25
12R22.5	16	ST 518	26	9.0	129.3	1,045.8	8.25
385/65R22.5	18	ST 520	32	12.0	128.0	1,035.2	11.75
425/65R22.5	20	ST 520	34	13.2	134.1	1,085.0	13.00
445/65R22.5	20	ST 520	42	14.2	137.4	1,111.8	14.00
11R22.5	16	ST 528	26	9.4	125.7	1,016.6	8.25
11R24.5	16	ST 528	26	9.4	132.1	1,068.4	8.25
315/80R22.5	20	ST 528	26	10.0	128.4	1,038.4	9.00
11R22.5	14	ST 710	22	8.4	125.3	1,013.4	8.25
11R22.5	16	ST 710	22	8.4	125.3	1,013.4	8.25
11R24.5	14	ST 710	22	8.4	131.6	1,064.2	8.25
11R24.5	16	ST 710	22	8.4	131.6	1,064.2	8.25
285/75R24.5	14	ST 710	24	8.4	125.4	1,014.4	8.25
295/75R22.5	14	ST 710	24	8.4	121.4	982.4	8.25
11R17.5	14	ST 717	22	7.7	110.1	890.6	8.25
13/80R20	18	ST 717	26	10.1	125.1	1,012.0	9.00
14/80R20	18	ST 717	26	11.1	130.0	1,051.8	10.00
9R17.5	14	ST 717	22	6.3	100.1	809.8	6.75
225/70R19.5	12	ST 718	22	7.2	95.9	775.8	6.75
245/70R19.5	12	ST 718	22	8.1	100.8	815.0	7.50
315/80R22.5	18	ST 718	26	9.8	128.8	1,041.6	9.00
385/65R22.5	18	ST 720	32	11.9	128.0	1,035.8	11.75
425/65R22.5	20	ST 720	34	13.1	134.1	1,085.0	12.25
445/65R22.5	20	ST 720	42	14.1	137.4	1,111.8	13.00
10.00R15	14	ST 727	20	7.4	109.8	888.4	7.50
10.00R20	14	ST 727	22	7.6	125.4	1,014.1	7.50
10.00R20	16	ST 727	22	7.6	125.4	1,014.1	7.50
10R17.5	16	ST 727	20	7.4	102.2	826.6	7.50
10R22.5	14	ST 727	20	7.2	121.6	983.9	7.50
11.00R20	16	ST 727	24	8.0	129.4	1,046.8	8.00
11R22.5	14	ST 727	20	7.6	125.4	1,014.1	8.25
11R22.5	16	ST 727	20	7.6	125.4	1,014.1	8.25
11R24.5	14	ST 727	22	7.6	131.6	1,064.9	8.25
11R24.5	16	ST 727	22	7.6	131.6	1,064.9	8.25
12.00R20	16	ST 727	22	8.4	134.0	1,083.6	8.50
12R22.5	16	ST 727	24	8.0	129.4	1,046.8	9.00
215/75R17.5	16	ST 727	18	7.2	92.3	746.4	6.00
255/70R22.5	16	ST 727	22	8.3	110.4	893.3	7.50
8.25R15	14	ST 727	18	6.4	99.9	807.8	6.50
8.25R20	14	ST 727	20	6.3	115.5	934.3	6.50

Size	PR	Pattern	Buffing Radius (Inch)	Finished Tread Width (Inch)	Circumferential measure at 4/32nd undertread (Inch)	Brk Diameter + 8/32nd (mm)	Rim Width (Inch)
9.00R20	12	ST 727	20	7.2	122.0	986.5	7.00
9R22.5	14	ST 727	18	6.7	115.9	937.2	6.75
10.00R20	14	ST 738	22	8.3	126.1	1,019.8	7.50
11R22.5	14	ST 738	22	8.3	126.1	1,019.8	8.25
11R22.5	16	ST 738	22	8.3	126.1	1,019.8	8.25
11R24.5	14	ST 738	22	8.3	132.3	1,070.6	8.25
11R24.5	16	ST 738	22	8.3	132.3	1,070.6	8.25
12R22.5	16	ST 738	24	8.8	129.2	1,044.8	9.00
285/75R24.5	14	ST 738	24	8.6	125.8	1,017.4	8.25
295/75R22.5	14	ST 738	24	8.6	121.4	982.4	9.00
11R22.5	14	ST 748A	22	8.3	125.7	1,016.6	8.25
11R22.5	16	ST 748A	22	8.3	125.7	1,016.6	8.25
11R24.5	14	ST 748A	22	8.3	132.1	1,068.4	8.25
11R24.5	16	ST 748A	22	8.3	132.1	1,068.4	8.25
285/75R24.5	14	ST 748A	24	8.6	125.8	1,017.4	8.25
295/75R22.5	14	ST 748A	24	8.6	121.4	982.4	9.00
11R22.5	14	ST 758	22	8.8	125.4	1,014.4	8.25
11R22.5	16	ST 758	22	8.8	125.4	1,014.4	8.25
11R24.5	14	ST 758	22	8.8	131.7	1,065.2	8.25
11R24.5	16	ST 758	22	8.8	131.7	1,065.2	8.25
285/75R24.5	14	ST 758	24	8.8	125.5	1,015.4	8.25
295/75R22.5	14	ST 758	24	8.8	121.3	981.4	9.00
385/65R22.5	18	ST 770	32	11.9	128.2	1,037.2	11.75
10.00R20	16	ST 900	22	8.7	126.2	1,020.6	7.50
11R22.5	16	ST 900	22	8.7	126.2	1,020.6	8.25
11R24.5	16	ST 900	22	8.7	132.4	1,071.4	8.25
12R22.5	16	ST 900	24	9.2	129.5	1,047.8	9.00
11R24.5	16	ST 901	24	8.9	131.5	1,064.0	8.25
10.00R20	14	ST 908	24	8.3	125.4	1,014.4	7.50
11R22.5	14	ST 908	24	8.3	125.6	1,016.4	8.25
11R22.5	16	ST 908	24	8.3	125.6	1,016.4	8.25
11R24.5	14	ST 908	24	8.3	131.9	1,067.2	8.25
11R24.5	16	ST 908	24	8.3	131.9	1,067.2	8.25
12R22.5	16	ST 908	24	9.1	129.4	1,046.8	9.00
255/70R22.5	16	ST 908	24	8.5	110.2	891.3	7.50
285/75R24.5	14	ST 908	24	8.3	126.0	1,019.5	8.25
295/75R22.5	14	ST 908	24	8.3	121.8	985.0	9.00
225/70R19.5	12	ST 918	20	7.6	95.9	775.8	6.75
245/70R19.5	14	ST 918	22	8.0	100.2	810.2	7.50
11R22.5	14	ST 928	24	8.7	125.4	1,014.4	8.25
11R22.5	16	ST 928	24	8.7	125.4	1,014.4	8.25
11R24.5	14	ST 928	24	8.7	131.6	1,064.9	8.25
11R24.5	16	ST 928	24	8.7	131.6	1,064.9	8.25
285/75R24.5	14	ST 928	26	8.7	125.5	1,015.4	9.00
295/75R22.5	14	ST 928	26	8.7	121.3	981.4	9.00