


Long Haul Series | Steer

- Flat Contact Technology reduces potential for irregular wear by controlling the shape and pressure distribution of the tire footprint.
- Shoulder grooves work with the wide, flat tread radius to control irregular wear.
- Micro sipes protect the interior ribs from punch wear.
- Even longer wearing tread compound on the outside, cool running base rubber compound on the inside.
- Stone ejectors protect the casing in base of the tread groove.
- Built with SmartWay Verified Technology.



The ST778+ SE is a SMARTWAY Verified long haul steer tire. Incorporating a collection of features, the ST778+ SE delivers superior miles to removal, excellent handling for safe operation and dependable retreadability of the Sumitomo casing.

ST778+ SE Featuring SmartWay Verified Technology

Product Code	Tire Size	Service Desc.	Load Range / Ply	Pref Rim Width (inch)	Min Rim Width (inch)	Single Max Load (lbs)	Dual Max Load (lbs)	I.P. (psi)	Overall Diameter (inch)	Section Width (inch)	Min Dual Spacing (inch)	Skid Depth (X/32")	Static Loaded Radius (inch)	Revs Per Mile	Max Speed (mph)
5532852	11R22.5	146/143L	H/16	8.25	7.50	6,610	6,005	120	41.5	11.3	12.5	18	19.3	501	75
5532859	11R24.5	149/146L	H/16	8.25	7.50	7,160	6,610	120	43.2	11.3	12.5	18	20.2	481	75
5532875	295/75R22.5	144/141L	G/14	9.00	8.25	6,175	5,675	110	40.1	11.5	13.2	18	18.8	518	75
5532878	285/75R24.5	144/141L	G/14	8.25	7.50	6,175	5,675	110	41.3	11.0	12.5	18	19.4	503	75

This company manufactures:

- EPA SmartWay verified technologies
- Verified equipment for SmartWay Certified Tractors - and /or
- Verified equipment for SmartWay Certified Trailers

As a result, we assist SmartWay partners with meeting their goals of energy efficiency and emissions reductions.

Learn more about...
SmartWay
www.epa.gov/smartway

