

Premium Series


Regional Steer



SUMITOMO TIRE **ST709**

Regional steers have to be durable across a broad range of conditions. ST709 is durable enough when there's serious work to be done, but versatile enough to display on-highway manners.

- Beefy 20/32nd" tread depth applied to a wide, flat casing for 10% more rubber volume than our predecessor design, for much longer life in high scuff applications.
- Chevron block center ribs with lateral sipes effectively cut water film on wet roads for enhanced traction and safety.
- Thick curbing ribs help shield the casing from sidewall damage.
- Stone ejectors protect the casing from damage in the base of the groove.
- An innovative design device helps control irregular wear during on-highway use.
- Suitable for high-speed regional transport, local P&D, school buses, equipment haulers, refuse trucks, and even urban dump trucks primarily operating on paved surfaces.



Product Code	Tire Size	Load Range Ply	Pref Rim Width (inch)	Min Rim Width (inch)	Single Max I.P. (psi)	Single Max Load (lbs)	Dual Max I.P. (psi)	Dual Max Load (lbs)	Overall Diameter (inch)	Section Width (inch)	Min Dual Spacing (inch)	Skid Depth (x/32")	Static Loaded Radius (inch)	Revs Per Mile	Max Speed (mph/kmh)
5532251	11R22.5	14/G	8.25	7.50	105	6,175	105	5,840	41.5	11.2	12.5	20	19.4	500	75/121
5532252	11R22.5	16/H	8.25	7.50	120	6,610	120	6,005	41.5	11.2	12.5	20	19.4	500	75/121
5532258	11R24.5	14/G	8.25	7.50	105	6,610	105	6,005	43.5	11.2	12.5	20	20.4	477	75/121
5532259	11R24.5	16/H	8.25	7.50	120	7,160	120	6,610	43.5	11.2	12.5	20	20.4	477	75/121
5532275	295/75R22.5	14/G	9.00	8.25	110	6,175	110	5,675	40.2	11.3	13.2	20	18.7	517	75/121
5532278	285/75R24.5	14/G	8.25	-	110	6,175	110	5,675	41.5	10.7	12.5	20	19.4	500	75/121