


SUMITOMO TIRE **ST727** | SUMITOMO TIRE **ST717** | SUMITOMO TIRE **ST738**

All Position Rib

These lines offer many hard to find sizes and ply ratings. Every tire is engineered to be Sumitomo tough.

- Sumitomo four steel belt casing construction resists punctures, increases vehicle stability, and contributes to more retread cycles.
- Application specific tread compound resists the effects of scuffing from sharp turns and gives long mileage.
- 5 rib design for better vehicle stability in all weather conditions.



* includes tube and flap



ST727

Product Code	Tire Size	Load Range Ply	Pref Rim Width (inch)	Min Rim Width (inch)	Single Max I.P. (psi)	Single Max Load (lbs)	Dual Max I.P. (psi)	Dual Max Load (lbs)	Overall Diameter (inch)	Section Width (inch)	Min Dual Spacing (inch)	Skid Depth (x/32")	Static Loaded Radius (inch)	Revs Per Mile	Max Speed (mph/kmh)
5530504	8.25R15*	14/G	6.50	7.00	120	4,080	120	3,860	33.1	9.3	10.6	14	15.5	627	65/105
5530507	10.00R15*	14/G	7.50	-	105	5,070	105	4,805	36.1	10.7	12.5	16	16.5	566	65/105
5530510	8.25R20*	14/G	6.50	7.00	120	4,940	120	4,675	37.9	9.1	10.6	16	17.8	546	65/105
5530513	9.00R20*	12/F	7.00	7.50	100	5,205	100	4,940	40.1	10.0	11.7	17	18.8	518	65/105
5530516	10.00R20*	14/G	7.50	8.00	105	6,175	105	5,840	41.2	10.9	12.5	17	19.2	506	65/105
5530517	10.00R20*	16/H	7.50	8.00	120	6,610	120	6,005	41.2	10.9	12.5	17	19.2	506	65/105
5530520	11.00R20*	16/H	8.00	8.50	120	7,390	120	6,780	42.5	11.5	13.0	18	19.9	490	65/105
5530523	12.00R20*	18/J	8.50	9.00	120	8,270	120	7,610	44.1	11.8	14.2	19	20.6	473	65/105
5530540	10R17.5	16/H	7.50	6.75	105	4,470	105	4,235	33.9	9.8	11.4	16	15.8	615	65/105
5530546	9R22.5	14/G	6.75	-	120	4,940	120	4,675	38.1	8.9	10.3	16	17.8	545	75/121
5530548	10R22.5	14/G	7.50	6.75	115	5,675	115	5,355	40.2	10.0	11.4	16	18.9	515	75/121
5530551	11R22.5	14/G	8.25	7.50	105	6,175	105	5,840	41.2	10.9	12.5	17	19.3	504	75/121
5530552	11R22.5	16/H	8.25	7.50	120	6,610	120	6,005	41.2	10.9	12.5	17	19.3	504	75/121
5530558	11R24.5	14/G	8.25	7.50	105	6,610	105	6,005	43.4	11.0	12.5	17	20.3	479	75/121
5530559	11R24.5	16/H	8.25	7.50	120	7,160	120	6,610	43.4	11.0	12.5	17	20.3	479	75/121
5530555	12R22.5	16/H	9.00	8.25	120	7,390	120	6,780	42.5	11.3	13.5	18	19.8	491	75/121
5530566	215/75R17.5	16/H	6.00	6.75	125	4,805	125	4,540	30.6	8.3	14.9	16	16.7	687	75/121
5530570	235/75R17.5	18/J	6.75	7.50	125	6,005	125	5,675	31.5	9.3	10.3	16	14.5	659	65/110
5530587	255/70R22.5	16/H	7.50	6.75	120	5,510	120	5,070	36.3	9.9	11.3	16	17.1	569	75/121
5530590	275/70R 22.5	16/H	8.25	7.50	120	7,000	120	6,395	37.8	10.9	11.9	17	17.5	549	75/121

ST717

5530426	13/80R20*	18/J	9.00	8.50	110	8,045	-	-	41.2	12.5	14.5	19	19.2	506	65/105
5530429	14/80R20*	18/J	10.00	9.00	120	9,090	-	-	43.0	13.5	-	20	19.8	491	65/105
5530438	9R17.5	14/G	6.75	6.00	120	4,080	120	3,860	33.1	8.9	10.3	16	15.4	632	65/105
5530442	11R17.5	14/G	8.25	7.50	105	5,050	105	4,805	36.4	11.7	12.6	17	16.7	582	65/105

st738

5530216	10.00R20*	14/G	7.50	8.00	105	6,175	105	5,840	41.5	11.1	12.5	18	19.3	504	75/121
5530255	12R22.5	16/H	9.00	8.25	120	7,390	120	6,780	42.5	11.2	13.5	18	19.7	494	75/121