

ST528

SUMITOMO TIRES

Heavy Series | Premium All Purpose

- Deeper tread depth increases time in service and provides more traction at all wheel positions.
- Application specific tread compounds resist tread chipping in high-scuff on and off road applications.
- Rust inhibitor compounds coat all interior steel belts and body ply components.
- Thick curbing ribs help shield the casing from sidewall damage.
- Stone ejectors protect the casing from damage in the base of the groove.
- Extra thick layer of undertread rubber protects the belt package.
- Sumitomo four steel belt casing construction resists punctures, increases vehicle stability and contributes to more retread cycles.



With its class-leading 26/32" tread depth on the standard sizes and the 10,200lbs. load carrying capacity on size 315/80R22.5, the ST528 is a Premium On and Off-Highway Mixed Service All-Position Tire.

Product Code	Tire Size	Service Desc.	Load Range / Ply	Pref Rim Width (inch)	Min Rim Width (inch)	Single Max Load (lbs)	Dual Max Load (lbs)	I.P. (psi)	Overall Diameter (inch)	Section Width (inch)	Min Dual Spacing (inch)	Skid Depth (X/32")	Static Loaded Radius (inch)	Revs Per Mile	Max Speed (mph)
5532052	11R22.5	146/143K	H/16	8.25	7.50	6,610	6,005	120	42.0	11.1	12.6	26	19.6	494	68
5532059	11R24.5	149/146K	H/16	8.25	7.50	7,160	6,610	120	44.1	11.1	12.6	26	20.5	471	68
5532063	315/80R22.5	157/154K	L/20	9.00	9.00	10,200	8,270	130	42.7	11.2	13.8	24	19.7	491	68

