


Premium Series | Long Haul Drive

- New tread pattern concept couples sophisticated traction and smooth even wear.
- Solid shoulders with rigid interior tread block configuration control heel/toe wear.
- Super-deep tread pattern applied across a wide, flat radius for remarkably long miles to removal.
- Diamond cut block edges fight irregular wear and resist cuts and snags.
- Increased base rubber dissipates heat while running at high speeds in long haul operations.

ST938SE

ST938



Cross-country or around town, ST938 is the next generation traction companion to ST778 and ST709. Because it was designed from the inside out to resist irregular wear and give high miles per /32", ST938 is incredibly long wearing. Its bold tread elements really bite, while its S-Tech Design casing yields outstanding long-term performance.

ST938SE Featuring SmartWay Verified Technology

Product Code	Tire Size	Load Range Ply	Pref Rim Width (inch)	Min Rim Width (inch)	Single Max I.P. (psi)	Single Max Load (lbs)	Dual Max I.P. (psi)	Dual Max Load (lbs)	Overall Diameter (inch)	Section Width (inch)	Min Dual Spacing (inch)	Skid Depth (x/32")	Static Loaded Radius (inch)	Revs Per Mile	Max Speed (mph/kmh)
5532752	11R22.5	16/H	8.25	7.50	120	6,610	120	6,005	42.2	11.1	12.5	26	19.7	492	75/121
5532759	11R24.5	16/H	8.25	7.50	120	7,160	120	6,610	44.1	11.3	12.5	26	20.6	471	75/121
5532775	295/75R22.5	14/G	9.00	8.25	110	6,175	110	5,675	40.6	11.3	13.2	26	19.0	512	75/121
5532778	285/75R24.5	14/G	8.25	8.25	110	6,175	110	5,675	42.0	10.6	12.5	26	19.7	495	75/121

ST938

Product Code	Tire Size	Load Range Ply	Pref Rim Width (inch)	Min Rim Width (inch)	Single Max I.P. (psi)	Single Max Load (lbs)	Dual Max I.P. (psi)	Dual Max Load (lbs)	Overall Diameter (inch)	Section Width (inch)	Min Dual Spacing (inch)	Skid Depth (x/32")	Static Loaded Radius (inch)	Revs Per Mile	Max Speed (mph/kmh)
5532452	11R22.5	16/H	8.25	7.50	120	6,610	120	6,005	42.3	11.3	12.5	30	19.7	491	75/121
5532459	11R24.5	16/H	8.25	7.50	120	7,160	120	6,610	44.3	11.4	12.5	30	20.7	469	75/121
5532475	295/75R22.5	14/G	9.00	8.25	110	6,175	110	5,675	40.8	11.5	13.2	30	19.0	509	75/121
5532478	285/75R24.5	14/G	8.25	8.25	110	6,175	110	5,675	42.1	11.0	12.5	30	19.7	493	75/121

This company manufactures:

- EPA SmartWay verified technologies
- Verified equipment for SmartWay Certified Tractors - and/or
- Verified equipment for SmartWay Certified Trailers

As a result, we assist SmartWay partners with meeting their goals of energy efficiency and emissions reductions.

Learn more about...
SmartWay
www.epa.gov/smartway