

SUMITOMO'S HTR SPORT H/P



High Performance SUV

- 1 Twin Reversible Sidewall Designs smooth sidewall for clean shiny appearances, serration style sidewall for more decorative look.
- 2 Two-in-One Shoulder Block Design provides for superb lateral grip, reduced irregular wear, maximum wet grip and stability.
- 3 Four Wide Deep Circumferential Grooves excellent anti-hydroplaning capabilities.
- 4 Jointless Nylon Band Technology promotes stable, predictable handling, excellent uniformity, and smooth ride.
- 5 Versatile Design for the plus sized look and the real world load requirements of SUVs and light trucks. Some sizes in reinforced construction.



HTR Sport H/P											UTQG - 480 A A			
Product Code	Tire Size	Service Description	Rim Range (inch)	Design Rim Width (inch)	PSI	Max Load (lbs)	Overall Diameter (inch)	Section Width (inch)	Tread Width (inch)	Tread Depth (X/32")	Loaded Radius (inch)	Rolling Circum. (inch)	Revs per Mile	Weight (lbs.)
5521412	285/60R18	116H	8.0-10.0	8.5	51	2,756	31.5	11.5	9.0	14	14.1	-	675	48.4
5521416	P275/60R20	114H	7.5-9.5	8.0	51	2,601	33.0	10.9	8.7	14	15.0	99.2	638	47.0
5521421	255/55R18	109H	7.0-9.0	8.0	50	2,271	29.0	10.0	8.7	14	13.2	-	728	39.6
5521426	275/55R20	117H	7.5-9.5	8.5	50	2,833	32.1	11.0	9.4	14	14.6	96.3	658	45.2
5521435	285/50R20	116H	8.0-10.0	9.0	50	2,756	31.3	11.2	9.8	14	14.3	-	673	46.2
5521437	305/50R20	120H	8.5-11.0	9.5	50	3,086	32.0	12.0	10.5	14	14.6	-	659	50.6
5521448	275/45R20	110H	8.5-10.0	9.0	50	2,337	29.8	10.6	9.2	14	13.7	-	700	39.6
5521450	P295/45R20	114H	9.5-11.0	10.0	50	2,601	30.4	11.6	9.8	14	13.9	-	687	44.0
5521454	285/45R22	114H	9.0-10.5	9.5	50	2,601	32.0	11.1	9.6	14	14.8	97.3	651	42.7
5521458	P305/45R22	118H	9.5-11.5	9.5	50	2,910	32.8	12.0	10.2	14	15.1	-	637	52.9
5521462	265/40R22	106H	9.0-10.5	9.5	50	2,094	30.3	10.6	9.5	14	14.2	92.6	684	37.9
5521468	305/40R22	114H	10.0-12.0	11.0	50	2,601	31.6	12.3	10.9	14	14.6	96.2	658	48.5
5521480	265/35R22	102H	9.0-10.5	9.5	50	1,874	29.3	10.6	9.6	14	13.8	89.8	705	36.4
5521482	285/35R22	106H	9.5-11.0	10.0	50	2,094	29.9	11.2	10.3	14	14.0	91.5	693	39.7
5521490	295/35R24	110H	10.0-11.5	10.0	50	2,337	32.2	11.7	10.6	14	15.1	98.4	643	43.8
5521492	305/35R24	112H	10.0-12.0	11.0	50	2,469	32.4	12.2	11.0	14	15.2	99.2	638	46.9

SAFETY WARNING - SUMITOMO TIRE DOES NOT RECOMMEND ANY PLUS FITMENT THAT HAS A LOWER LOAD INDEX THAN THE ORIGINAL EQUIPMENT TIRES. FAILURE TO FOLLOW PUBLISHED LOAD AND INFLATION SPECIFICATIONS IS VERY DANGEROUS.